



- - - - - AREA DI LAVORO \ WORKING AREA  
 ———— PORTATA CON LIMITATORE DI MOMENTO \ LIFT WITH LOAD LIMIT VALVE  
 ———— PORTATA PROLUNGHE MANUALI \ MANUAL EXTENSIONS LIFT

**P 3500 L**

**P 3500 L/3SI**

massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. / max. hydraulische Reichweite	6.25 m		7.80 m	
minimo sfilo idraulico / min. hydraulic outreach / min. alcance hidraulico / rallonge hydraulique min./ min. hydraulische Reichweite	3.25 m		3.30 m	
altezza massima / max height above installation level / altura max. desde el filo infer. de la base / hauteur de levage au dessus du plan de pose / hubhöhe ab Fahrzeugrahmen	7.88 m		9.36 m	
portate gru base / outreach - lifting capacity / alcances hidraulicos - capacidad / extension - charge hydraulische Reichweite - Hubkraft	3.25 m	990 kg	3.30 m	970 kg
	4.75 m	700 kg	4.80 m	620 kg
	6.25 m	520 kg	6.30 m	450 kg
			7.80 m	350 kg
portata prolunga manuale / outreach with manual extens. - lifting capacity / alcances con prolongas manuales - capacidad extension avec rallonges manuelles - charge / Reichweite mit manuellen / Verlängerungen - Hubkraft	7.85 m	360 kg	9.40 m	250 kg
	9.45 m	260 kg		
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada / debit d'huile recommandé Förderleistung der Hydraulikpumpe	12 l/min		12 l/min	
pressione di lavoro / working pressure / presión de trabajo / pression de travail / Betriebsdruck	290 bar		290 bar	
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite / Inhalt des Öltanks	21 l		21 l	
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / Schwenkbereich	402°		402°	
coppia di rotazione / slewing torque / momento de giro / couple de rotation / Drehmoment	3.6 kNm		3.6 kNm	
altezza a riposo / height in folded position / hauteur en position repliee / altura en posición de reposo/ Höhe ab Fahrzeugrahmen zusammengelegt	1630 mm		1630 mm	
larghezza a riposo / width in folded position / largeur en position repliee / anchura en posición de reposo/ Breite zusammengelegt	1980 mm		2080 mm	
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl-manuell seitlich ausziehbare Abstützungen	<b>490 kg</b>		<b>535 kg</b>	