



P 7200 L

P 7200 L/3SI

massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. / max. hydraulische Reichweite	7.00 m		8.78 m	
minimo sfilo idraulico / min. hydraulic outreach / min. alcance hidraulico / rallonge hydraulique min. / min. hydraulische Reichweite	3.60 m		3.68 m	
altezza massima / max height above installation level / altura max. desde el filo infer. de la base / hauteur de levage au dessus du plan de pose / hubhöhe ab Fahrzeugrahmen	9.00 m		10.75 m	
portata gru base / outreach - lifting capacity / alcances hidraulicos - capacidad / extention - charge hydraulische Reichweite - Hubkraft	3.60 m	1980 kg	3.68 m	1730 kg
	5.30 m	1270 kg	5.38 m	1110 kg
	7.00 m	920 kg	7.08 m	800 kg
			8.78 m	630 kg
portata prolunga manuale / outreach with manual extens. - lifting capacity / alcances con prolongas manuales - capacidad extention avec rallonges manuelles - charge / Reichweite mit manuellen / Verlängerungen - Hubkraft	8.85 m	630 kg	10.63 m	450 kg
	10.70 m	460 kg	12.48 m	340 kg
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada / debit d'huile recommandé Förderleistung der Hydraulikpumpe	20 l/min		20 l/min	
pressione di lavoro / working pressure / presión de trabajo / pression de travail / Betriebsdruck	260 bar		260 bar	
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite / Inhalt des Öltanks	45 l		45 l	
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / Schwenkbereich	402°		402°	
coppia di rotazione / slewing torque / momento de giro / couple de rotation / Drehmoment	8 kNm		8 kNm	
altezza a riposo / height in folded position / hauteur en position repliee / altura en posición de reposo/ Höhe ab Fahrzeugrahmen zusammengelegt	2000 mm		2000 mm	
larghezza a riposo / width in folded position / largeur en position repliee / anchura en posición de reposo/ Breite zusammengelegt	2200 mm		2200 mm	
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl.-manuell seitlich ausziehbare Abstützungen	910 kg		985 kg	

- - - - - AREA DI LAVORO \ WORKING AREA
 ——— PORTATA CON LIMITATORE DI MOMENTO \ LIFT WITH LOAD LIMIT VALVE
 ——— PORTATA PROLUNGHE MANUALI \ MANUAL EXTENSIONS LIFT

Ing. BONFIGLIOLI S.p.A. BOLOGNA - ITALIA

tel 051/6867214 fax 051/6867222 e-mail: cranes@ingbonfiglioli.it